
## Ranch

SILENCER Ranch Model (also available in the extended model) includes a patented full-opening head and tail doors providing 26" of clearance so full-term cows and herd bulls enter and exit the chute without hanging up their lower bodies. Designed for a wide range of livestock sizes and weight.

#### Specifications >



Length	100"
Width	48"
Height	93"
Approx. Weight (lbs.)	2495
Mainframe	4" x 2" x 1/8", rectangular tubing, 2" x 2" square tubing
Cylinders	(5) 4 x 2 cylinders, (1) 2 x 6-cylinder, main cylinder pins greaseable
Head & Tail Doors	Full-opening and fully sheeted
Overall Outside Length	102"
Overall Inside Length	91"
Side Gates	1/8" wall
SILENCER Pump Weight	235 lbs.
Head & Tailgate Height	67 1/2"
Inside Chute Height	67 1/2"
Total Width (Doors Open)	67"
Total Width Doors Closed (including hydraulic levers)	59"
Fitted Hoses	Yes
30ft of Extension Hose	Yes
Reinforced Construction	Yes
Primed Before Painted	Yes
Oil-based Urethane Bearings	Yes
130 Polyethylene Contact Points	Yes
Standard 3 Spool Hydraulic Valves	Yes



# **Heavy Duty**

SILENCER Heavy-Duty model (also available in the extended model) is designed for increased chute life with reinforced construction, modular construction for superior maintenance, and replaceable heavy-duty drop bars. This model can take a beating!

Perfect for lots of use and larger animal traffic.


< Specifications

Length	100"
Width	48"
Height	93"
Approx. Weight (lbs.)	3095
Mainframe	4" x 2" x 3/16", rectangular tubing, 2" x 2" square tubing
Cylinders	(6) 4 x 2 cylinders, (1) 2 x 6 cylinder, (8) main cylinder pins greaseable
Head & Tail Doors	Full-opening and fully sheeted
Overall Outside Length	102"
Overall Inside Length	91"
Side Gates	1/8" wall
SILENCER Pump Weight	235 lbs.
Head & Tailgate Height	67 1/2"
Inside Chute Height	67 1/2"
Total Width (Doors Open)	67"
Total Width Doors Closed (including hydraulic levers)	59"
Fitted Hoses	Yes
30ft of Extension Hose	Yes
Reinforced Construction	Yes
Primed Before Painted	Yes
Oil-based Urethane Bearings	Yes
130 Polyethylene Contact Points	Yes
Standard 3 Spool Hydraulic Valves	Yes
Floor	1/4" floor for increased life of chute
Modular construction for superior maintenance	Yes
Replaceable heavy-duty drop bars	Yes
Bearings and Connectors	8 quick-change, re-lube roller bearings - top connectors and lower head door connector
Standard 3 Spool Hydraulic Valves	Yes

## **Commercial Pro**

SILENCER Commercial Pro model (also available in the extended model) is designed for high volume and heavy usage of cattle through the chute. It is designed to be extra durable to allow for longer and more reliable use. The commercial pro model is best suited for large volume cattle operations.

### Specifications >



Longth	102"
Length	
Width	48"
Height	93"
Approx. Weight (lbs.)	4015
Mainframe	4" x 3" x 5/16", rectangular tubing, 2" x 2" square tubing
Cylinders	(5) 4 x 2 cylinders, (1) 2 x 6 cylinder, main cylinder pins greaseable
Head & Tail Doors	Full-opening and fully sheeted; wedge tail doors
Overall Outside Length	102"
Overall Inside Length	91"
Side Gates	1/4" wall, extra neck access
SILENCER Pump Weight	235 lbs.
Head & Tailgate Height	67 1/2"
Inside Chute Height	67 1/2"
Total Width (Doors Open)	67"
Total Width Doors Closed (including hydraulic levers)	59"
Fitted Hoses	Yes
30ft of Extension Hose	Yes
Reinforced Construction	Yes
Primed Before Painted	Yes
Oil-based Urethane Bearings	Yes
130 Polyethylene Contact Points	Yes
Standard 3 Spool Hydraulic Valves	Yes
Floor	1/4" floor for increased life of chute
Modular construction for superior maintenance	Yes
Replaceable heavy-duty drop bars	Yes
Bearings and Connectors	8 quick-change, re-lube roller bearings - top connectors and lower head door connector
Extra neck access side	Optional